

PAT-NO: JP359209438A
DOCUMENT-IDENTIFIER: JP 59209438 A
TITLE: FORMING DEVICE OF CIRCULAR
RING
PUBN-DATE: November 28, 1984

INVENTOR-INFORMATION:

NAME	COUNTRY
IZUMITANI, MASATAKA	
YOSHII, KENJI	

ASSIGNEE-INFORMATION:

NAME	COUNTRY
TOPY IND LTD	N/A

APPL-NO: JP58081716
APPL-DATE: May 12, 1983

INT-CL (IPC): B21D053/30 , B21D022/16 ,
B21H001/06

US-CL-CURRENT: 72/101

ABSTRACT:

PURPOSE: To prevent occurrence of buckling during forming of a circular ring by advancing and retreating inner rolls in axial direction and tilting the roll shaft from horizontality in vertical plane in forming a material ring by an

outer roll and inner rolls.

CONSTITUTION: A material ring 21 is pressure held between inner rolls 30, 31, and expanded. Inner rolls 30, 31 are tilted by the action of cylinders 35, 36, and the ring is rotated while applying large compressive force to the upper part of the ring 21. The ring 21 is tilted in vertical direction by a cylinder 39, and pressed position is changed to circumferential direction. An outer roll 10 is pressed down, and both end parts of the ring 21 is pressed between flange part forming rolls 12, 13. Then, an eccentric shaft 14 is rotated by the action of a cylinder 29, and a drop part forming roll 11 is pressed down relatively against flange part forming rolls 12, 13. At this time, the drop part forming roll of inner rolls 30, 31 keeps the gap to the drop part forming roll 11 of outer roll 10 automatically in the thickness of the material ring by deformation of an elastic member 42. Thus, no reduction of thickness is caused in the material ring 21.

COPYRIGHT: (C)1984,JPO&Japio